



PCT/GB 2003 / 0 0 2 3 2 7



INVESTOR IN PEOPLE

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

REC'D 16 JUL 2003

WIPO

PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.


Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 1 July 2003

Patents Form 1/77

Patents Act 1977
(Rule 16)



Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP9 1RH

1. Your reference	P6841GB		
2. Patent application number <i>(The Patent Office will fill in this part)</i>	0213667.9		
3. Full name, address and postcode of the or of each applicant <i>(underline all surnames)</i>	Richard Alan METCALFE Bridgestone Surveyors, 2nd Floor, Clayton House 59 Piccadilly Gardens, Manchester, M1 2QR		
Patents ADP number <i>(if you know it)</i>	8401804001		
If the applicant is a corporate body, give the country/state of its incorporation			
4. Title of the invention	Trim for a Wheel Rim		
5. Name of your agent <i>(if you have one)</i>	L. J. Bray & Co.		
"Address for service" in the United Kingdom to which all correspondence should be sent <i>(including the postcode)</i>	Raw Holme Midgehole Road HEBDEN BRIDGE West Yorkshire HX7 7AF		
Patents ADP number <i>(if you know it)</i>	04054565001		
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and <i>(if you know it)</i> the or each application number	Country	Priority application number <i>(if you know it)</i>	Date of filing <i>(day / month / year)</i>
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing <i>(day / month / year)</i>	
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? <i>(Answer 'Yes' if:</i> a) <i>any applicant named in part 3 is not an inventor, or</i> b) <i>there is an inventor who is not named as an applicant, or</i> c) <i>any named applicant is a corporate body.</i> <i>See note (d))</i>	No		

TRIM FOR A WHEEL RIM

The present invention relates to a trim for a wheel rim and in particular but not exclusively, to a protective trim
5 for an alloy wheel rim of a vehicle.

Alloy wheel rims for automobiles are expensive accessories which can be easily damaged if the wheel of the vehicle strikes or grazes a kerbstone or other similar
10 obstruction. Protective wheel trims are known which can be fitted to a wheel assembly to cover the annular edge of a wheel rim. These trims may be provided solely for aesthetic reasons but some also provide some degree of protection to the edge of the wheel rim. However, many of them suffer from
15 the disadvantage that they interfere with the fitting of the tyre to the rim and some affect the sealing fit between the tyre and the wheel rim. Such interference may be dangerous if the seal is in danger of being breached and as a consequence may contravene national and international standards which
20 control the interface between automobile tyres and their rims for safety reasons.

The object of the present invention is to provide a trim for a wheel rim which does not interfere with the aforesaid
25 interface and which will provide some degree of protection for the wheel rim against impact damage.

According to the present invention there is provided a trim for a wheel rim comprising an annulus with an inturned
30 outer rim to define radial and axial faces, which can be located over and around an outer lip of the wheel rim, and a plurality of grippers spaced around the circumference of the outer rim by means of which the trim can be secured to the wheel rim. and a resilient insert which is located around the

Preferably, the outer rim is inturned at 90° to the outer radial face of the annulus.

- 5 Preferably also, the grippers are integrally formed with the inturned outer rim of the annulus.

Preferably also, the grippers comprise tangs which can be deformed so that they bite into an axial outer face of the
10 wheel rim to secure the trim to the wheel rim. Advantageously, each gripper is substantially rectangular or trapezoidal and defines a tang at each of its projecting corners.

- 15 Preferably also, at least six grippers are provided equidistantly spaced around the annulus.

Preferably also, the surface of the insert adapted to contact the wheel rim is coated with an adhesive to provide
20 an additional means of securement for the trim.

Preferably also, the inner rim of the annulus is at least partially inturned.

- 25 Preferably also, the resilient insert is moulded in position on the inner side of the annulus.

Preferably also, the outer surface of the insert is contoured so as to be complementary in shape to the outer lip
30 of a wheel rim over which it is intended to be fitted.

Preferably also, the annulus is made from rolled and pressed stainless steel.

- 35 Preferably also, the insert comprises a rubber or other similarly resilient material.

An example of the present invention will now be described by way of example with reference to the accompanying drawing, in which:-

5

Fig. 1 is a sectional view of a trim according to the invention operatively positioned on wheel rim;

Fig. 2 is a perspective view of a section of the trim shown in Fig. 1 before attachment to the wheel rim; and

10

Fig. 3 is a schematic side view, to a reduced scale, of the trim to show the location of grippers which form an integral part thereof.

15

A wheel assembly of a vehicle, as shown in Fig. 1 comprises a wheel rim 1 defining an outwardly projecting flange 2. The inner side of the flange 2 thereby forms a seating to receive and seal with a tyre bead 3. The outer side of the flange 2 is conventionally provided with a projecting lip 4. A trim 5 according to the present invention is adapted to be secured to the wheel rim 1 to cover and thereby provide a degree of protection for the lip 4.

20

The trim 5 comprises an annulus 6 which may be formed from bright rolled and pressed stainless steel or other suitable material. The annulus 6 is provided with an inturned outer rim 7, which is preferably inturned at 90° so that the annulus 6 thereby defines radial and axial faces. These faces locate over and around the projecting lip 4 of the wheel rim 1. The inner rim 8 of the annulus 6 is also at least partially inturned to provide a safe edge for handling the trim 5 and also to improve the appearance of the trim 5 when in use.

30

While the annulus 6 could be manufactured by being pressed from a steel sheet, it is more easily manufactured by being pressed from a steel strip and then rolled to form the annular shape with the aforementioned cross-sectional profile. The adjoining ends of the strip can then be joined together by welding using a conventional welding process such as electron beam or laser welding.

The outer rim 7 of the trim 5 provided with a plurality of grippers 9, which are integrally formed with and equidistantly spaced around the circumference of the outer rim 7 as shown in Fig. 3. Preferably, at least six grippers 9 are provided by means of which the trim can be secured to the wheel rim 1. The grippers 9 comprise curving rectangular or trapezoidal members that define tangs 10 with sharp edges at their projecting corners. By elastically deforming the grippers 9, for example by hammering around the rim in an axial direction using a soft-faced hammer, the sharp edges of the tangs 10 can be made to bite into the axial outer face 11 of the flange 2 of the wheel rim 1 to secure the trim 5 in position over the lip 4.

A resilient insert 12 is located around the radial and axial faces defined by the inner side of the annulus 6 in order to cushion the trim 5 against the wheel rim 1. The insert 12 preferably comprises a rubber or other similarly resilient material. While the insert 12 could be push-fitted into position into the curving interior defined by the inner side of the annulus 5, preferably it is moulded *in situ* by injection moulding or similar conventional process. As different models of automobiles and alloy wheel trims have slightly different profiles, preferably the outer surface of the insert is contoured as at 13 so as to be complementary in shape to the projecting lip 4 of the wheel rim 1 over which it is intended to be fitted. This spreads the load of any impact over a larger portion of the rim 1 and thereby

provides a better cushioning effect, with actual damage to the rim 1 being less likely if the impact is only minor. The insert 12 also aids the fitting of the trim 5 to the wheel rim 1.

5

In order to assist in the securement of the trim 5 to the wheel rim 1, the exposed surface 14 of the insert 12 that is adapted to contact the wheel rim 1 is coated with an adhesive. The adhesive may be a rapid-curing or contact
10 adhesive that is applied manually immediately before fitment of the trim 5 the wheel rim 1. Alternatively, the adhesive may be applied when the trim 5 is manufactured and covered by a peelable release liner (not shown) that can be peeled off to expose the adhesive immediately prior to fitment.

15

Fitment of the trim 5 to a vehicle wheel rim 1 is accomplished by locating the trim 5 over the projecting lip 4 of a wheel rim so that the insert 12 can adhere closely to the apposed surface of the lip 4 and the wheel rim 1 and so
20 that at least one and preferably two grippers 9 are in close contact with the axial outer face 11 of the flange 2 of the wheel rim 1. The other grippers 9 can then be hammered into gripping contact with the face 11 by a hide-faced hammer or similar tool.

CLAIMS

1. A trim for a wheel rim comprising an annulus with an
inturned outer rim to define radial and axial faces,
5 which can be located over and around an outer lip of the
wheel rim, and a plurality of grippers spaced around the
circumference of the outer rim by means of which the
trim can be secured to the wheel rim, and a resilient
insert which is located around the radial and axial
10 faces defined on the inner side of the annulus to
cushion the trim against the wheel rim.
2. A trim as claimed in Claim 1, wherein the outer rim is
inturned at 90° to the outer radial face of the annulus.
15
3. A trim as claimed in Claim 1 or Claim 2, wherein the
grippers are integrally formed with the inturned outer
rim of the annulus.
- 20 4. A trim as claimed in any of Claims 1 to 3, wherein the
grippers comprise tangs which can be deformed so that
they bite into an axial outer face of the wheel rim to
secure the trim to the wheel rim.
- 25 5. A trim as claimed in Claim 4, wherein each gripper is
substantially rectangular and defines a tang at each of
its projecting corners.
6. A trim as claimed in any of Claims 1 to 5, wherein at
30 least six grippers are provided equidistantly spaced
around the annulus.
7. A trim as claimed in any of Claims 1 to 6, wherein
35 surface of the insert adapted to contact the wheel rim
is coated with an adhesive to provide an additional
means of securement for the trim.

8. A trim as claimed in any of Claims 1 to 7, wherein the inner rim of the annulus is at least partially inturned.
- 5 9. A trim as claimed in any of Claims 1 to 8, wherein the resilient insert is moulded in position on the inner side of the annulus.
- 10 10. A trim as claimed in any of Claims 1 to 9, wherein the outer surface of the insert is contoured so as to be complementary in shape to the outer lip of a wheel rim over which it is intended to be fitted.
- 15 11. A trim as claimed in any of Claims 1 to 10, wherein the annulus is made from rolled and pressed stainless steel.
- 20 12. A trim as claimed in any of Claims 1 to 11, wherein the insert comprises a rubber or other similarly resilient material.
13. A trim for a wheel rim substantially as described herein with reference to the accompanying drawing.

ABSTRACT

A trim (5) for a wheel rim (1), in particular an alloy wheel rim for a vehicle comprises an annulus (6) with an
5 intumed outer rim (7) to define radial and axial faces, which can be located over and around an outer lip (4) of the wheel rim (1). A plurality of grippers (9) are spaced around the circumference of the outer rim (7) by means of which the trim (5) can be secured to the wheel rim (1). A resilient
10 insert (12) is located around the radial and axial faces defined on the inner side of the annulus (6) to cushion the trim (5) against the wheel rim (1).




Fig. 1




Fig. 2




Fig. 3